

## HX Series - Recessed Mounted

Exceptional performance powered  
by Ecopower Air Technology.



### ***Specification Text / Tender Text***

#### **> Coils**

Units with water heating coils are manufactured from copper tube, mechanically expanded to die cut aluminium fins with female BSP connections. Factory tested to 20 bar air under water testing and rated for working pressures of up to 8 bar. Externally mounted mid-position valve offers no heat (ambient), half heat or full heat settings.

#### **> Casing**

Galvanised steel enclosure with stiffening bars to provide rigidity to the unit and to prevent distortion and drumming.

#### **> Outlet / Discharge Grills**

An active cellular grille to shape the air as it passes through the grille, that serves as a hinged access panel for maintenance.

#### **> Fans**

Modular fan decks with 2-3 high temperature plastic impellers driven by a permanent split capacitor motor are used to maximise air stream uniformity. Multiple speeds are possible through the use of tapings on the motor.

## > Filters

A woven plastic mesh over welded metal frame filter is inserted to sit on top of the air intake grille to reduce the ingress of dirt and dust, protecting the unit's internals.

## > Controls

The HX Series uses a factory installed intelligent, controller with the following features included:

- Multiple fan speed selection - 3 speeds available
- Multiple heating level selection - 3 levels available (Water and Electric units only)
- Dry contact for supervisory system connection or door switch
- Programmable input for air temperature thermostat
- Thermal protection reset
- Master/slave control
- Wall Controller - Durable injection moulded ABS housing, contains the printed circuit board. Rubberised buttons to provide user adjustment of 3 fan speeds, 3 heat levels, on/off switch and automatic/manual heating control.
- Optional Modbus and Bacnet interface module for easy connection to a BMS system.

## > Electric Heating Elements (Electric Units Only)

Factory installed and wired, thermally protected and constructed with a galvanised steel frame, with helical coil suspended elements. Elements are typically powered with 3 phase with single phase options available on request.

## > Ceiling Mounting Bracket

The unit is supplied with holes and internal bracketry to allow the unit to be ceiling mounted on M10 drop rods.

**IF YOU ARE LOOKING FOR MORE INFORMATION YOU CAN ASK OUR DEDICATED TEAM OR DOWNLOAD OUR BROCHURE AND MANUAL.**



[CLICK TO SPEAK TO TEAM](#)



[CLICK TO DOWNLOAD THE BROCHURE](#)



[CLICK TO DOWNLOAD THE MANUAL](#)

> **+44 (0) 24 7638 4646**

> **SALES@THERMOSCREENS.COM**

> **WWW.THERMOSCREENS.COM**

Thermoscreens Limited St Mary's Road, Nuneaton, Warwickshire CV11 5AU

Part of  
**CARVER**  
CLIMATE SYSTEMS